



Eaves

Hips


Roadstone Eave Ventilation (with soffit)



Roadstone Eave Ventilation (without soffit)




Roadstone Dry Hip




*HIP BATTEN HEIGHT TABLE

Tile profile	rafter pitch	batten height mm
Spanish Roll	22.5° - 35°	135
	36.0° - 55°	125
Double Roman	22.5° - 35°	130
	36.0° - 55°	120
Flat Tiles	22.5° - 30°	115
	31.0° - 55°	105

Bedded Hip



Lead Valley



Lead Valley (max. 6m on plan)

- Roadstone standard tile (profile as selected) cut to rake of valley
- 47mm x 35mm tiling batten
- Roofing underlay
- 12mm valley boards to extend 225mm min. each side of valley
- Bedding mortar (3 sharp sand : 1 cement)
- Undercloak slate separating mortar from lead
- Code 5 lead lining (max. length 1.5m) dressed over tilting fillet and welled*

*Lead to be lapped 220mm when rafter pitch is 25° and below.
*Lead to be lapped 150mm for pitches above 25°.


Abutments

Abutments

Chimney Abutment

(back gutter)

- Code 4 lead cover flashing
- Roadstone standard tile (profile as selected)
- Roofing underlay (carried into gutter)
- Code 4 lead lining carried under tile and welled
- 25mm timber boards to support lead gutter
- 50mm x 50mm timber support




Chimney Abutment


(front flashing)

- Code 4 lead cover flashing
- Code 4 lead flashing over top tile
- 47mm x 35mm tiling batten
- Roofing underlay


Rooflight Abutment




Side Abutment with Profiled Tiles



Side Abutment with Flat Tiles




Top Edge Abutment




Verge


Roadstone Stepped Dry Verge



Roadstone Continuous Dry Verge




Roadstone Bedded Verge



Ridge


Roadstone Dry Vent Ridge



*RIDGE BATTEN HEIGHT TABLE

Tile profile	rafter pitch	batten height mm
Spanish Roll	22.5° - 35°	100
	36.0° - 50°	75
Double Roman	22.5° - 35°	75
	36.0° - 50°	50
Flat Tiles	22.5° - 30°	50
	31.0° - 55°	25


Roadstone Rapid Roll-Out Ridge



*RIDGE BATTEN HEIGHT TABLE

Tile profile	rafter pitch	batten height mm
Spanish Roll	22.5° - 35°	100
	36.0° - 50°	75
Double Roman	22.5° - 35°	75
	36.0° - 50°	50
Flat Tiles	22.5° - 30°	50
	31.0° - 55°	25


Bedded Ridge



Mansard


Plain / Cladding Tiles

Mansard




- Roadstone standard tile (profile as selected)
- 47mm x 35mm tiling batten
- Tile clip
- 47mm x 35mm batten to support tile and engage tile clip
- Roofing underlay continued over mansard
- Timber fillet to support lead flashing
- Code 4 lead flashing welted under eave tile and dressed over top tile

Ventilated Eave (with soffit)



- Standard tile
- Roofing underlay
- 47mm x 35mm tiling batten
- Eave tile
- PVC ventilation ducting tray continued into gutter
- Fascia grille (nailed to fascia board) with a PVC apron lapped under roofing underlay


Bedded Ridge



- 450mm concrete half round ridge tile
- Bedding mortar (3 sharp sand : 1 cement)
- Continuous edge bedding (solid only at joints)
- Tile slips supporting bedding mortar
- Top tile
- Standard tile
- 47mm x 35mm tiling batten
- Roofing underlay lapped over ridge apex


Sprocket

Sprocket




- Roadstone standard tile (profile as selected)
- Roofing underlay lapped over lead flashing
- Code 4 lead flashing welted under upper tile and dressed over lower tile
- Timber fillet to support lead flashing
- 47mm x 35mm tiling batten
- Roofing underlay finished under lead flashing

Abutment to Projecting Frame




- 47mm x 35mm counter batten
- Code 4 lead fixed to counter batten and dressed to window frame
- Roofing underlay
- 47mm x 35mm tiling batten
- Mastic bead
- Tile and half
- Standard tile

Abutment to Flush Frame



- 47mm x 35mm counter batten
- Roofing underlay
- Pointed mortar bedding (3 sharp sand : 1 cement)
- 47mm x 35mm tiling batten
- Tile and half
- Standard tile

Abutment to Brickwork



- Code 4 lead fixed to counter batten, welted and dressed into brickwork
- Brickwork
- 47mm x 35mm counter batten
- Roofing underlay
- 47mm x 35mm tiling batten
- Tile and half
- Standard tile